

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00540

PN: **280073**



OGM PLUS 00540VCEPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, EPDM, PEEK, ceramic

signal output (standard): 5.0 ml/pulse, 200 pulses/l

max. pump size: 54 / 85 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/706008/24322/1001

ECOLAB Engineering GmbH  
D-83313 Siegedorf



Anlaufgrenze 6,0 [l/h]\*  
lower measuring range limit

Impulszahl 30 [n/min]  
pulse rate

bei 10,0 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 02.11.2022

Prüfer Sollereder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00540

PN: **280073**



OGM PLUS 00540VCEPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, EPDM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 85 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/708008/24322/1002

ECOLAB Engineering GmbH  
D-83313 Siegedorf



Anlaufgrenze 6,0 [l/h]\*  
lower measuring range limit

Impulszahl 34 [n/min]  
pulse rate

bei 10,0 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 02.11.2022

Prüfer Sollerseder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00540

PN: **280073**



OGM PLUS 00540VCEPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, EPDM, PEEK, ceramic

signal output (standard): 5.0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/706008/24322/1003

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



Anlaufgrenze 6,0 [l/h]\*  
lower measuring range limit

Impulszahl 34 [n/min]  
pulse rate

bei 10,0 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 02.11.2022

Prüfer Sollerseder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00540

PN: 280073



OGM PLUS 00540VCEPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, EPDM, PEEK, ceramic

signal output (standard): 5.0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/706008/24322/1004

ECOLAB Engineering GmbH  
D-83313 Stegedorf



Anlaufgrenze 6,0 [l/h]\*  
lower measuring range limit

Impulszahl 30 [n/min]  
pulse rate

bei 10,0 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 02.11.2022

Prüfer Sollerseder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00540

PN: **280073**

OGM PLUS 00540VCEPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, EPDM, PEEK, ceramic

signal output (standard): 5.0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/70E008/24322/1005

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



Anlaufgrenze 6,0 [l/h]\*  
lower measuring range limit

Impulszahl 34 [n/min]  
pulse rate

bei 10,0 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 02.11.2022

Prüfer Sollerseder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00540

PN: **280073**

OGM PLUS 00540VCEPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, EPDM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/706008/24322/1008

ECOLAB Engineering GmbH  
D-83313 Siegedorf



Anlaufgrenze 6,0 [l/h]\*  
lower measuring range limit

Impulszahl 30 [n/min]  
pulse rate

bei 10,0 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 02.11.2022

Prüfer Sollereder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00540

PN: 280073

OGM PLUS 00540VCEPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, EPDM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/706008/24322/1007

ECOLAB Engineering GmbH  
D-83313 Siegedorf



Anlaufgrenze 6,0 [l/h]\*  
lower measuring range limit

Impulszahl 34 [n/min]  
pulse rate

bei 10,0 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 02.11.2022

Prüfer Sollerseder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00540

PN: 280073

OGM PLUS 00540VCEPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, EPDM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/708008/24322/1008

ECOLAB Engineering GmbH  
D-83313 Siegedorf



Anlaufgrenze 6,0 [l/h]\*  
lower measuring range limit

Impulszahl 32 [n/min]  
pulse rate

bei 10,0 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 02.11.2022

Prüfer Sollereder



# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00540

PN: **260073**



OGM PLUS 00540VCEPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, EPDM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code:

01/706008/24322/1006

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



Anlaufgrenze 6,0 [l/h]\*  
lower measuring range limit

Impulszahl 31 [n/min]  
pulse rate

bei 10,0 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 02.11.2022

Prüfer Pollereder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00540

PN: **280073**



OGM PLUS 00540VCEPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, EPDM, PEEK, ceramic  
signal output (standard): 5.0 ml/pulse, 200 pulses/l  
max. pump size: 54 / 65 l/h (50/60Hz)  
semiconductor junction: PNP  
prod. code: 01/708008/24322/1010

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



Anlaufgrenze 6,0 [l/h]\*  
lower measuring range limit

Impulszahl 30 [n/min]  
pulse rate

bei 10,0 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 02.11.2022

Prüfer Sollereder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00540

PN: **280073**



OGM PLUS 00540VCEPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, EPDM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/706008/24322/1011

ECOLAB Engineering GmbH  
D-63313 Siegedorf



Anlaufgrenze 6,0 [l/h]\*  
lower measuring range limit

Impulszahl 30 [n/min]  
pulse rate

bei 10,0 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 02.11.2012

Prüfer Sollnereder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00540

PN: 280073



OGM PLUS 00540VCEPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, EPDM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/708008/24322/1012

ECOLAB Engineering GmbH  
D-83313 Siegedorf



Anlaufgrenze 6,0 [l/h]\*  
lower measuring range limit

Impulszahl 31 [n/min]  
pulse rate

bei 10,0 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 02.11.2022

Prüfer Sollerseder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00540

PN: **280073**



OGM PLUS 00540VCEPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, EPDM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 85 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/706006/24322/1013

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



Anlaufgrenze 6,0 [l/h]\*  
lower measuring range limit

Impulszahl 34 [n/min]  
pulse rate

bei 10,0 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 02.11.2022

Prüfer Sollereder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00540

PN: **280073**

OGM PLUS 00540VCEPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, EPDM, PEEK, ceramic

signal output (standard): 5.0 ml/pulse, 200 pulses/l

max. pump size: 54 / 85 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/706008/24322/1014

ECOLAB Engineering GmbH  
D-83313 Siegsdorf



Anlaufgrenze 6,0 [l/h]\*  
lower measuring range limit

Impulszahl 32 [n/min]  
pulse rate

bei 10,0 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 02.11.2022

Prüfer Soller edler

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00540

PN: 280073



OGM PLUS 00540VCEPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, EPDM, PEEK, ceramic

signal output (standard): 5.0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/708008/24322/1015

ECOLAB Engineering GmbH  
D-83113 Siegsdorf



Anlaufgrenze 6,0 [l/h]\*  
lower measuring range limit

Impulszahl 31 [n/min]  
pulse rate

bei 10,0 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 02.11.2022

Prüfer Sollereder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00540

PN: 280073



OGM PLUS 00540VCEPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, EPDM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 85 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/706006/24322/1016

ECOLAB Engineering GmbH  
D-83313 Slegsdorf



Anlaufgrenze 6,0 [l/h]\*  
lower measuring range limit

Impulszahl 33 [n/min]  
pulse rate

bei 10,0 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 02.11.2022

Prüfer Sollersdor



# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00540

PN: 280073



OGM PLUS 00540VCEPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, EPDM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/708008/24322/1017

ECOLAB Engineering GmbH  
D-83313 Stegsdorf



Anlaufgrenze 6,0 [l/h]\*  
lower measuring range limit

Impulszahl 31 [n/min]  
pulse rate

bei 10,0 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 02.11.2022

Prüfer Sollereder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00540

PN: **280073**



OGM PLUS 00540VCEPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, EPDM, PEEK, ceramic

signal output (standard): 5.0 ml/pulse, 200 pulses/l

max. pump size: 54 / 85 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/708008/24322/1018

ECOLAB Engineering GmbH  
D-83313 Siegedorf



Anlaufgrenze 6,0 [l/h]\*  
lower measuring range limit

Impulszahl 32 [n/min]  
pulse rate

bei 10,0 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 02.11.2022

Prüfer Sollereder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00540

PN: **280073**

OGM PLUS 00540VCEPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, EPDM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 85 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/706008/24322/1019

ECOLAB Engineering GmbH  
D-83313 Stegedorf



Anlaufgrenze 6,0 [l/h]\*  
lower measuring range limit

Impulszahl 32 [n/min]  
pulse rate

bei 10,0 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 02.11.2022

Prüfer Sollgeder

# Prüfprotokoll OGM<sup>plus</sup>

Oval gear meter PLUS 00540

PN: **280073**

OGM PLUS 00540VCEPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, EPDM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/706008/24322/1020

ECOLAB Engineering GmbH  
D-83313 Siegedorf



Anlaufgrenze 6,0 [l/h]\*  
lower measuring range limit

Impulszahl 33 [n/min]  
pulse rate

bei 10,0 [l/h]\*  
at

\* = kontinuierlicher Durchfluss / continuous flow

Datum 02.11.2022

Prüfer Solleseder