

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0.38 ml/pulse, 2600 pulses/l

max. pump size: 11.2 / 13.5 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01 / 493873 / 41322 / 1001

ECOLAB Engineering GmbH

D-83313 Siegedorf



280162



Anlaufgrenze 0.8 [l/h]*
lower measuring range limit

Impulszahl 52 [n/min]
pulse rate

bei 1.25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 07.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,38 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01 / 493873 / 41322 / 1002



260162

ECOLAB Engineering GmbH
D-83313 Siegsdorf



Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 52 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 07.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction:	PVC, FKM HF, PVDF, ceramic
signal output (standard):	0,36 ml/pulse, 2600 pulses/l
max. pump size:	11,2 / 13,5 l/h (50/60Hz)
semiconductor junction:	PNP
prod. code:	01 / 493873 / 41322 / 1003

280162

ECOLAB Engineering GmbH
D-83313 Siegsdorf

Anlaufgrenze 08 [l/h]*
lower measuring range limit

Impulszahl 53 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 07.06.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,38 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01 / 493873 / 41322 / 1004

ECOLAB Engineering GmbH
D-83313 Slegsdorf



280162



Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 53 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 07.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/81-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic
signal output (standard): 0.36 ml/pulse, 2800 pulses/l
max. pump size: 11.2 / 13.5 l/h (50/60Hz)
semiconductor junction: PNP
prod. code: 01 / 493873 / 41322 / 1005

ECOLAB Engineering GmbH
D-63313 Siegsdorf



260162

Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 53 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 07.04.22

Prüfer **P 410**

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8I-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,38 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60-Hz)

semiconductor junction: PNP

prod. code: 01 / 493873 / 41322 / 1006

ECOLAB Engineering GmbH
D-83313 Siegedorf



280162



Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 50 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 07.06.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112



W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic
signal output (standard): 0,36 ml/pulse, 2600 pulses/l
max. pump size: 11,2 / 13,5 l/h (50/60Hz)
semiconductor junction: PNP
prod. code: 01 / 493873 / 41322 / 1007

280162

ECOLAB Engineering GmbH
D-83313 Siegsdorf



Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 51 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 07.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8I-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,38 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01 / 493873 / 41322 / 1008

ECOLAB Engineering GmbH
D-83313 Slegsdorf



280162



Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 53 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 07.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic
signal output (standard): 0,38 ml/pulse, 2600 pulses/l
max. pump size: 11,2 / 13,5 l/h (50/60-Hz)
semiconductor junction: PNP
prod. code: 01 / 493873 / 41322 / 1009

ECOLAB Engineering GmbH
D-63313 Siegbach



280162



Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 56 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 07.06.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/6i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,36 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60-Hz)

semiconductor junction: PNP

prod. code: 01 / 493873 / 41322 / 1010

ECOLAB Engineering GmbH

D-83313 Slegsdorf



280162



Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 51 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 07.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262908

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic
signal output (standard): 0,38 ml/pulse, 2600 pulses/l
max. pump size: 11,2 / 13,5 l/h (50/60Hz)
semiconductor junction: PNP
prod. code: 01 / 493873 / 41322 / 1011

ECOLAB Engineering GmbH
D-63313 Siedsdorf



280162



Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 53 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 06.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906



OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic
signal output (standard): 0,38 ml/pulse, 2600 pulses/l
max. pump size: 11,2 / 13,5 l/h (50/60Hz)
semiconductor junction: PNP
prod. code: 01 / 493873 / 41322 / 1012

280162

ECOLAB Engineering GmbH
D-63313 Siegsdorf



Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 52 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 06.06.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/6i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic
signal output (standard): 0,38 ml/pulse, 2600 pulses/l
max. pump size: 11,2 / 13,5 l/h (50/60Hz)
semiconductor junction: PNP
prod. code: 01 / 493873 / 41322 / 1013

ECOLAB Engineering GmbH
D-83313 Siegedorf



280162

Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 53 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 06.06.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112



W3T262906

OGM PLUS 00112VCFPPVKE-G1/81-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic
signal output (standard): 0,38 ml/pulse, 2600 pulses/l
max. pump size: 11,2 / 13,5 l/h (50/60-Hz)
semiconductor junction: PNP
prod. code: 01 / 493873 / 41322 / 1014

260162

ECOLAB Engineering GmbH
D-83313 Siegsdorf



Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 56 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 06.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112



W3T262906

OGM PLUS 00112VCFPPVKE-G1/BI-99-2600p-P

materials of construction:	PVC, FKM HF, PVDF, ceramic
signal output (standard):	0,38 ml/pulse, 2600 pulses/l
max. pump size:	11,2 / 13,5 l/h (50/60Hz)
semiconductor junction:	PNP
prod. code:	01 / 493673 / 41322 / 1015

260162

ECOLAB Engineering GmbH
D-83313 Siegsdorf



Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 54 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 06.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,38 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01 / 493873 / 41322 / 1016

ECOLAB Engineering GmbH
D-83313 Siegsdorf



260162



Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 50 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 06.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2800p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0.38 ml/pulse, 2800 pulses/l

max. pump size: 11.2 / 13.5 l/h (50/60-Hz)

semiconductor junction: PNP

prod. code: 01 / 493873 / 41322 / 1017

ECOLAB Engineering GmbH
D-83313 Slegsdorf



280163



Anlaufgrenze 0.8 [l/h]*
lower measuring range limit

Impulszahl 51 [n/min]
pulse rate

bei 1.25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 06.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic
signal output (standard): 0,36 ml/pulse, 2600 pulses/l
max. pump size: 11,2 / 13,5 l/h (50/60-Hz)
semiconductor junction: PNP
prod. code: 01 / 493873 / 41322 / 1018

ECOLAB Engineering GmbH
D-83313 Siegedorf



280162



Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 52 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 06.04.22

Prüfer **P 410**

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/BI-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,38 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60-Hz)

semiconductor junction: PNP

prod. code: 01 / 493873 / 41322 / 1019

ECOLAB Engineering GmbH
D-83313 Siegsdorf



280162



Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 51 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 06.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic
signal output (standard): 0,38 ml/pulse, 2600 pulses/
max. pump size: 11,2 / 13,5 l/h (50/60-Hz)
semiconductor junction: PNP
prod. code: 01 / 493873 / 41322 / 1020

280162

ECOLAB Engineering GmbH
D-83313 Siegsdorf

Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 54 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 06.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/81-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,36 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01 / 493873 / 41322 / 1021

ECOLAB Engineering GmbH
D-83313 Siegsdorf



280162



Anlaufgrenze 08 [l/h]*
lower measuring range limit

Impulszahl 54 [n/min]
pulse rate

bei 125 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 06.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic
signal output (standard): 0,38 ml/pulse, 2600 pulses/l
max. pump size: 11,2 / 13,5 l/h (50/60-Hz)
semiconductor junction: PNP
prod. code: 01 / 493873 / 41322 / 1022

ECOLAB Engineering GmbH
D-83313 Siegsdorf



260162



Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 50 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 06.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/BI-99-2600p-P

materials of construction:	PVC, FKM HF, PVDF, ceramic
signal output (standard):	0,38 ml/pulse, 2600 pulses/l
max. pump size:	11,2 / 13,5 l/h (50/60Hz)
semiconductor junction:	PNP
prod. code:	01 / 493873 / 41322 / 1023

280162

ECOLAB Engineering GmbH
D-83313 Siegsdorf

Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 51 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 06.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906



OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,38 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01 / 493873 / 41322 / 1024

280162

ECOLAB Engineering GmbH
D-83313 Siegsdorf



Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 55 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 06.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-90-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic
signal output (standard): 0,38 ml/pulse, 2600 pulses/l
max. pump size: 11,2 / 13,5 l/h (50/60-Hz)
semiconductor junction: PNP
prod. code: 01 / 493873 / 41322 / 1025

ECOLAB Engineering GmbH
D-83313 Siegsdorf



280162



Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 51 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 06.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic
signal output (standard): 0,38 ml/pulse, 2600 pulses/l
max. pump size: 11,2 / 13,5 l/h (50/60Hz)
semiconductor junction: PNP
prod. code: 01 / 499873 / 41322 / 1026



260162

ECOLAB Engineering GmbH
D-83313 Siegsdorf



Anlaufgrenze 08 [l/h]*
lower measuring range limit

Impulszahl 50 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 06.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic
signal output (standard): 0,38 ml/pulse, 2600 pulses/l
max. pump size: 11,2 / 13,5 l/h (50/60Hz)
semiconductor junction: PNP
prod. code: 01 / 493879 / 41322 / 1027

ECOLAB Engineering GmbH
D-63313 Siegbach



260162



Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 55 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 06.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2600p-P

materials of construction:	PVC, FKM HF, PVDF, ceramic
signal output (standard):	0,38 ml/pulse, 2600 pulses/l
max. pump size:	11,2 / 13,5 l/h (50/60Hz)
semiconductor junction:	PNP
prod. code:	01 / 493873 / 41322 / 1028

ECOLAB Engineering GmbH
D-83313 Siegsdorf



260162



Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 52 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 06.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112

W3T262906

OGM PLUS 00112VCFPPVKE-G1/6i-99-2600p-P

materials of construction: PVC, FKM HF, PVDF, ceramic

signal output (standard): 0,38 ml/pulse, 2600 pulses/l

max. pump size: 11,2 / 13,5 l/h (50/60-Hz)

semiconductor junction: PNP

prod. code: 01 / 493873 / 41322 / 1029

ECOLAB Engineering GmbH
D-63313 Siegedorf



260162



Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 52 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 06.04.22

Prüfer P 410

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00112



W3T262906

OGM PLUS 00112VCFPPVKE-G1/8i-99-2800p-P

materials of construction:	PVC, FKM HF, PVDF, ceramic
signal output (standard):	0,38 ml/pulse, 2800 pulses/l
max. pump size:	11,2 / 13,5 l/h (50/60-Hz)
semiconductor junction:	PNP
prod. code:	01 / 493873 / 41322 / 1030

280162

ECOLAB Engineering GmbH
D-83313 Siegsdorf



Anlaufgrenze 0,8 [l/h]*
lower measuring range limit

Impulszahl 52 [n/min]
pulse rate

bei 1,25 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 06.04.22

Prüfer P 410