

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**

OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1001

ECOLAB Engineering GmbH
D-83313 Siegedorf



Anlaufgrenze 6,00 [l/h]*
lower measuring range limit

Impulszahl 35 [n/min]
pulse rate

bei 10,00 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollwieseder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**

OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5.0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704992/14322/1002

ECOLAB Engineering GmbH
D-83313 Siegsdorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 33 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollervell

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**



OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60-Hz)

semiconductor junction: PNP

prod. code: 01/704932/14922/1003

ECOLAB Engineering GmbH
D-93313 Siegsdorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 34 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollereder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**

OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5.0 ml/pulse, 200 pulses/l

max. pump size: 54 / 85 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1004

ECOLAB Engineering GmbH
D-83313 Siegedorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 30 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer 

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**

OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1005



ECOLAB Engineering GmbH
D-83313 Siegsdorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 33 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollerseder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**

OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 95 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1006

ECOLAB Engineering GmbH
D-83313 Siegedorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 34 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26-10-2022

Prüfer Sollweider

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**

OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 85 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1007

ECOLAB Engineering GmbH
D-83313 Siegedorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 34 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollereder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**



OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 85 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1008

ECOLAB Engineering GmbH
D-83313 Siegedorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 32 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollereder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: 280043



OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1009

ECOLAB Engineering GmbH
D-83313 Slegendorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 33 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollerseder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**



OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5.0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1010

ECOLAB Engineering GmbH
D-83313 Siegedorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 32 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollereder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**

OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1011

ECOLAB Engineering GmbH

D-83313 Siegedorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 33 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollereder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**



OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5.0 ml/pulse, 200 pulses/l

max. pump size: 54 / 85 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1012

ECOLAB Engineering GmbH
D-83313 Slegedorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 31 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollereder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**



OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5.0 ml/pulse, 200 pulses/l

max. pump size: 54 / 85 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704992/14322/1013

ECOLAB Engineering GmbH
D-83313 Siegsdorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 30 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollereder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**



OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic
signal output (standard): 5.0 ml/pulse, 200 pulses/l
max. pump size: 54 / 85 l/h (50/60Hz)
semiconductor junction: PNP
prod. code: 01/704932/14322/1014

ECOLAB Engineering GmbH
D-63313 Siegedorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 33 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollnereder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**

OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 85 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1015

ECOLAB Engineering GmbH
D-83313 Slegendorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 34 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollereider

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: 280043



OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1016

ECOLAB Engineering GmbH
D-83313 Siegedorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 34 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollereder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**

OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 85 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1017

ECOLAB Engineering GmbH
D-83313 Slegsdorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 31 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollereder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**



OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704832/14322/1018

ECOLAB Engineering GmbH
D-63313 Siesdorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 33 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollerseder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**

OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 85 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01 / 704932 / 14322 / 1019

ECOLAB Engineering GmbH
D-83313 Stegedorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 30 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26-10-2022

Prüfer Sollgeseder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**



OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1020

ECOLAB Engineering GmbH
D-63313 Biegedorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 31 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.22

Prüfer Sollereder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**



OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1021

ECOLAB Engineering GmbH
D-83313 Siegedorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 33 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollereder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**



OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5.0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1022

ECOLAB Engineering GmbH
D-63313 Siegbach



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 34 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollereder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**



OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1023

ECOLAB Engineering GmbH
D-83313 Siegedorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 31 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26. 10. 2022

Prüfer Sollereder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**

OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5.0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1024

ECOLAB Engineering GmbH
D-83313 Siegedorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 31 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollereder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**



OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 85 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1025

ECOLAB Engineering GmbH
D-83313 Siegsdorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 32 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollerseder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**



OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5.0 ml/pulse, 200 pulses/l

max. pump size: 54 / 85 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1026

ECOLAB Engineering GmbH
D-83313 Slegsdorf



Anlaufgrenze 6.0 [l/h]*
lower measuring range limit

Impulszahl 30 [n/min]
pulse rate

bei 10.0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollereder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: 280043



OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code:

01/704932/14322/1027

ECOLAB Engineering GmbH
D-83313 Siegedorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 33 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollereder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**



OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5.0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1028

ECOLAB Engineering GmbH
D-83313 Siegedorf



Anlaufgrenze 60 [l/h]*
lower measuring range limit

Impulszahl 31 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollereder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: **280043**



OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5,0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1.020

ECOLAB Engineering GmbH
D-83313 Slegsdorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 32 [n/min]
pulse rate

bei 10,0 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sullereder

Prüfprotokoll OGM^{plus}

Oval gear meter PLUS 00540

PN: 280043



OGM PLUS 00540VCFPPKKE-G1/4I-99-0005m-P

materials of construction: PVC, FPM, PEEK, ceramic

signal output (standard): 5.0 ml/pulse, 200 pulses/l

max. pump size: 54 / 65 l/h (50/60Hz)

semiconductor junction: PNP

prod. code: 01/704932/14322/1030

ECOLAB Engineering GmbH
D-83313 Siegedorf



Anlaufgrenze 6,0 [l/h]*
lower measuring range limit

Impulszahl 33 [n/min]
pulse rate

bei 190 [l/h]*
at

* = kontinuierlicher Durchfluss / continuous flow

Datum 26.10.2022

Prüfer Sollreider