



Reliable Metering with ELADOS® EMP II E60

- ▲ Metering operation adjustment
- ▲ Automatic degassing
- ▲ Safety function

▲ Metering operation adjustment



▲ Automatic degassing



▲ Safety function



ELADOS® EMP II E60
1.4 to 24 l/h

From ready for connection and premounted metering stations up to the complete program of accessories:



OGM^{PLUS} Oval Gear Meter

- ▶ Intelligent and exact quantity metering and reliable process monitoring
- ▶ Automatic calibration function
- ▶ Consumption data acquisition
- ▶ Metering readjustment
- ▶ Independent of viscosity relative increment
- ▶ Adjustable pulse rate
- ▶ Plug & Flow for ELADOS[®] EMP E60



DEGAS^{PLUS}

Automatic degassing valve

- ▶ No more metering problems with gassing products
- ▶ Direct control by pump-software (ELADOS[®] EMP E60)
- ▶ Individual and simple operation by pump menu (ELADOS[®] EMP E60)
- ▶ Plug & Play for ELADOS[®] EMP E60



Multi-function valve

- ▶ **4 in 1** for cost savings (pressure control function, pressure relief function, manual degassing function, drain function)

- ▶ Maximum process reliability
- ▶ Simple installation
- ▶ Easy operation

Possible combinations for your reliable metering:

EMP II E60 combined with

- ▲ DEGAS^{PLUS} for automatic venting
- ▲ Multi-function valve
- ▲ Oval Gear Meter for metering operation monitoring

EMP II E60 combined with

- ▲ DEGAS^{PLUS} for automatic venting
- ▲ Multi-function valve

